

# HANDLINE NOZZLES



MYSTERY®

## Mystery®

The Mystery® Nozzle incorporates a twist-type shut-off, opening in straight stream and producing a flow from straight stream to wide fog. In combination with a B-375A ball shut-off, the Mystery® Nozzle promotes an extremely convenient method of advancing hoselines. Simply close the ball shut-off, remove the Mystery® tip, attach additional hose, and then reattach the tip at the end of the line. The tip's built-in shut-off allow for the line to be advanced rapidly without bringing in an additional nozzle.

HANDLINE NOZZLES


1-15



Base Size	AVAILABLE STANDARD FLOW RATE GPM (LPM)							Break-Apart Components	GRIP	SHUT-OFF	HANDLE	BASE	TEETH	DIMENSIONS		Model	Figure				
	60 (227)	95 (360)	125 (473)	170 (644)	200 (757)	250 (946)	Length (Inches)							Weight (Lbs.)							
	PSI (BAR)																				
100 (6.89)	100 (6.89)	75 (5.17)	100 (6.89)	100 (6.89)	50 (3.45)	75 (5.17)	100 (6.89)	Smooth Bore**	Pistol Grip	Twist	Ball	Tab	Horseshoe	Rigid	Swivel	Free Swivel	Cut Metal				
1.5"	•	•	•	•						•				s			s	4.625	1.375	L-205-BA (Tip Only)	1
	•	•	•	•				L-205-BA + LB-275A		•	•	o	s	o	s	o	s	8.50	3.50	LB-275-AF	2
			•		•	•	•			•	•	o	s	o	s	o	s	7.125	3.25	205-BA (Tip Only)	1
			•		•	•	•	205-BA + B-375AT	•	•	•	o	s	o	s	o	s	12.875	6.25	B-375-ATF*	3
			•		•	•	•	205-BA + B-375GAT	•	•	•	o	s		o	s	s	13.25	6.75	B-375-GATF*	3
2.5"			•		•	•				•				s			s	7.50	3.50	D-205-BA (Tip Only)	1
			•		•	•	•	D-205BA + JB-275A		•	•		s			s	s	13.625	7.50	JB-275-LAFD	4

Key s = standard o = option  
 \* Listed flow rate for break-apart nozzle with integral smooth bore is for Mystery® nozzle tip only.  
 \*\* 15/16" discharge standard on 1.5" base; 7/8", 1", 1 1/8", 1 1/4" available. Smooth bore discharge size may restrict flow of Mystery® tip.

## MYSTERY® CONFIGURATIONS

<b>Figure 1</b>	 <b>TIP ONLY</b> <i>Fig. 1</i>	<b>Figure 3</b>	 <b>BREAK-APART WITH INTEGRAL SMOOTH BORE</b> <i>(Shown with optional pistol grip)</i> <i>Fig. 3</i>
<b>Figure 2</b>	 <b>BREAK-APART</b> <i>Fig. 2</i>	<b>Figure 4</b>	 <b>LAFD NOZZLE</b> <i>Fig. 4</i>

OPTIONS	
HANDLES	
TAB	HORSESHOE
	
THREADS	
<p>All nozzles are NHT unless otherwise specified. See index T-12 for optional base threads, including British instantaneous.</p>	
BREAK-APART COMPONENTS	
<p>Ball shut-offs and/or playpipes referenced here may be found on page 1-24.</p>	

Figures depict general product types only and are not intended to be inclusive of all product features.