

# Traditional

- Elkhart's oldest line of monitors, trusted for decades
- Flexible installation options
  - Extensive base choices
  - Control options
    - Tiller control with continuous 360° rotation and positive twist-lock mechanism
    - Single hand-wheel control with continuous 360° rotation and positive twist-lock mechanism
    - Dual hand-wheel control with continuous 360° rotation
  - Hydrant mounting available
- Wide vertical travel range, including some models with a full 150° range
- All models are solidly constructed of rugged, corrosion-resistant cast brass with some models available in Elk-O-Lite®



Dual hand-wheel control features rotating base

360° rotation

Chrome-plated trim

Cast Brass construction (Elk-O-Lite® optional on some models)





## TRADITIONAL

SPECIFICATIONS					
Max. GPM (LPM)	1100 (4165) (See table for specifics)				
Inlets	Sizes		Types		
	6"	150# ANSI Flange			
	4"	150# ANSI Flange	300# ANSI Flange	NPT (F)	
	3"	150# ANSI Flange	300# ANSI Flange	NPT (F)	
	2.5"	150# ANSI Flange	300# ANSI Flange	NPT (F)	NHT (F)
Outlet	2.5"				NHT
Controls	Tiller				
	Single hand-wheel				
	Dual hand-wheel				
Materials / Finish	Brass or Elk-O-Lite® with red urethane enamel and chrome-plated trim				
Friction Loss – 292-6/293-6	32 psi at 750 gpm				
	14 psi at 500 gpm				
Friction Loss – 294-11	49 psi at 1100 gpm				
	25 psi at 750 gpm				
Travel	Variable (see table for specifics)				
Weight	Variable (see table for specifics)				
Ratings and Certifications	FM Approved, CE				

### KEY CONFIGURATIONS (ACCESSORIES)



292-6

(1)



294-11

(2)

### ADDITIONAL INFORMATION

- Marine Brass (85-5-5-5) construction is available on some models. Please inquire with our sales staff.
- All flanges specified with the monitor are flat faced. Raised face flanges are available with some inlet sizes. Please inquire with our sales staff.
- Other threads may be available. See index T-12 for optional threads.
- Hydrant models – hydrant swivel connection attaches to hydrant nipple. 6H models include elbow assembly and support rods.

### Traditional Selector Guide

MONITOR TYPE	Inlet Sizes (Inches)												Out-let	Max GPM	Controls				Certifications	Materials		Travel		Dimensions (Inches)			Illustration	Model					
	NHT		NPT			150# ANSI Flange				300# ANSI Flange					2.5"	1100 (4164)	750 (2839)	Dual Hand-wheel		Single Hand-wheel	Tiller Bar	CE	FM Approved	Brass	Elk-O-Lite®	Vertical			Horizontal	Height	Width	Weight (Lbs.)	
	2.5 Swivel		2.5	3	4	2.5	3	4	6	2.5	3	4																					6
Std		o	o	o	o	o	s	o	o	o	o		•	•			•	•	•			130°	360°	18.50	13.75	46	1	292-6					
Hyd	s												•	•			•	•	•			130°	360°	18.50	13.75	64		292-6H					
Std		o	o	o	o	o	s	o	o	o	o		•	•			•	•	•			150°	360°	18.50	13.75	53		293-6					
Std		o	o	o	o	o	s	o	o	o	o		•	•			•	•	•			150°	360°	18.50	13.75	53		293-6A					
Hyd	s												•	•			•	•	•			150°	360°	18.50	13.75	85		293-6H					
Std			o	o	o	o	s	o	o	o	o		•	•			•	•	•			150°	360°	26.25	16.75	114	2	294-11					
																2		1										Illus.					

KEY s = standard o = option  
Std = Standard Hyd = Hydrant

### Components & Options Chart

COMPONENTS & OPTIONS		ILLUSTRATION	MODEL
Companion Flange Kits	3" 150# ANSI steel flange with bolts and gasket		81315001
	4" 150# ANSI steel flange with bolts and gaskets		81317001
Drain Valve	Automatic ball drip drain valve		702

### Recommended Products

HF-500 – HYDRO-FOAM	CJN-B – SELECT-O-STREAM®	J – MYSTERY®	181 – DELUGE TIP	282B – STREAM SHAPER	296 – HYDRANT BASE	84 – BUTTERFLY WAFER VALVE
						
Page 6-14	Page 6-10	Page 6-12	Page 1-29	Page 1-27	Page 5-73	Page 5-73